

DECLARATION OF PERFORMANCE

No. 29DOP-2022-EN

1. Unique identification code of the product type:

CROSSIN HARD 36

PCC Prodex piana zamkniętokomórkowa natryskowa o niskiej gęstości

2. Intended use:

Construction Products:

In-situ formed sprayed rigid polyurethane (PUR) foam products.

Intended uses:

Thermal insulation of walls, ceilings, roofs and suspended ceilings.

3. Manufacturer:

PCC Prodex Sp. z o.o.
56-120 Brzeg Dolny, Poland
str.. Henryka Sienkiewicza 4

4. System(s) of assessment and verification of constancy of performance:

System 3

5. Harmonized standard:

EN 14315-1:2013

6. Notified bodies:

Instytut Techniki Budowlanej (1488)
Forschungsinstitut für Wärmeschutz (0751)

7. Declared performance:

Table 1 Declared Performance

Essential characteristics according to EN 14315-1:2013	Performance characteristics	Declared level/class
Reaction to fire	Reaction to fire	E
Water permeability	Short-term water absorption by partial immersion, W_p	0,10 kg/m ²
Thermal resistance	Declared thermal conductivity coefficient, λ_D	0,021 W/mK
Water vapor permeability	Water vapor diffusion resistance coefficient, μ	≥ 60
Compressive strength	Compressive stress at 10% relative deformation, σ_{10}	CS(10/Y)200
Durability of reaction to fire against ageing/degradation	Durability of properties	Does not deteriorate over time
Durability of thermal resistance against ageing/degradation	Thermal conductivity coefficient λ_D taking into account aging	For thickness: $d_N < 80$ mm $\lambda_D = 0,026$ W/(m·K) For thickness: $80 \text{ mm} \leq d_N < 120$ mm $\lambda_D = 0,025$ W/(m·K) For thickness: $d_N \geq 120$ mm $\lambda_D = 0,024$ W/(m·K)
	Thermal resistance R_D taking into account aging	Refer to table 2
	Dimensional stability	DS(70,90)3 DS(-20,-)3
Durability of compressive strength against ageing/degradation	Durability of properties	Does not decrease with time (remains constant or increases due to air diffusion into foam cells)
Continuous glowing combustion	Continuous glowing combustion	NPD

Table 2 Declared thermal resistance depending on the thickness of the product

λ_D [W/(m·K)]	0,026	0,026	0,026	0,026	0,026	0,026	0,025	0,025	0,025	0,025
d [mm]	30	35	40	50	60	70	80	88	90	100
R_D [(m ² K)/W]	1,172	1,367	1,563	1,953	2,344	2,734	3,200	3,500	3,600	4,000
λ_D [W/(m·K)]	0,025	0,024	0,024	0,024	0,024	0,024	0,024	0,024	0,024	0,024
d [mm]	110	120	130	140	150	160	170	180	190	200
R_D [(m ² K)/W]	4,400	5,000	5,417	5,833	6,250	6,667	7,083	7,500	7,917	8,333
λ_D [W/(m·K)]	0,024	0,024	0,024	0,024	0,024	0,024	0,024	0,024	0,024	0,024
d [mm]	210	220	230	240	250	260	270	280	290	300
R_D [(m ² K)/W]	8,750	9,167	9,583	10,000	10,417	10,833	11,250	11,667	12,083	12,500

The performance of the product identified above is in line with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer above.

On behalf of the manufacturer signed by:

Magdalena Wasieleska
Technologist

Brzeg Dolny 19.12.2022

PCC PRODEX Spółka z o.o.
Technolog
M. Wasieleska
Magdalena Wasieleska

